

adjust **Abii**

roof ladder

Telescopic Multi Purpose & Roof Access Ladder

adjustability



roofability



Facts and stats

Adjustability weight:	15.30kg (33.81lbs)
Roofability weight:	11.92kg (26.34lbs)
Stored size:	Length 1530mm Width 425mm Depth 265mm Base stabiliser 715mm wide
Height as stepladder:	1170mm min. 1950mm max.
Height as ladder:	2550mm min. 4130mm max.
Height as roof access ladder:	1300mm min. 3200mm max.
Adjustments:	280mm increments/rung spacings
Maximum load:	150kg (23.5 stone)
Classification:	EN131

Training and risk assessments

The regulations and HSE require that operatives are trained and a risk assessment is conducted for all work at height.

Note: **Ability International Limited is a training provider accredited to BS EN ISO 9001:2000 and the National Britannia SAFEcontractor scheme.**

Applications and use

For: Chimney sweeps, flue liners, inspections and other chimney requirements.

TV aerial and satellite dish installations.

Loft access and inspections.

Decorating and general access.

Price effective April 2006 (excluding VAT) £248.00
Carriage (inclusive UK mainland)

Price includes 1 no. Cambuckle Strap for tying-in the Abil ladder.

ABILITY INTERNATIONAL LTD, WARMINGTON, NR. PETERBOROUGH PE8 6TZ (UK).

TEL: +44 (0) 1832 226445

www.abilityint.com

FAX: +44 (0) 1832 226398

e-mail: sales@abilityint.com

Committed to Standards

