

FASE

Fall Arrest Safety Equipment

For Chimney Sweeps
& Chimney Engineers



5m FASE - Sling Pack - comprising :-

1 no. RGK 26/5 5m Chimney Sling (5m operating length)	£ 44.31
1 no. RGH 2 Safety harness with front & rear "D" rings	£ 78.11
1 no. RGA 1 Inertia reel retractable Mini Block - up to 2.75m length - with 2no. screw gate karabiners	£ 85.61
	£208.03

Price list 1st November 2008 + carriage + VAT

Technical Data

D Ring Fixings - heat treated zinc coated high tensile alloy steel. MBS 30kN

Web Material - 45mm close weave water resistant polyester

Fittings - High tensile alloy steel. MBS 22kN

Weight -1.5kg

Accredited to EN361

Sizing - Universal fitting

Web colour - Black & yellow



6m FASE - Safety Pack - comprising :-

1 no. RGK 26/6 6m Chimney Sling (6m operating length)	£ 48.75
1 no. RGH 2 Safety harness with front & rear "D" rings	£ 78.11
1 no. RGA 1 Inertia reel retractable Mini Block - up to 2.75m length - with 2no. screw gate karabiners	£ 85.61
	£212.47

Price list 1st November 2008 + carriage + VAT

SAFETY GUIDE

1. Chimney Fall Arrest Safety Equipment should only be used after the condition of the chimney stack has been considered suitable for anchorage. If in doubt DO NOT USE,
2. Only one person should be attached to a Chimney Sling at any one time. Use extra Chimney Slings for extra persons.
3. Slings, Harnesses & Mini Blocks should be issued on a personal basis.
4. Visually inspect the condition of webbing, stitch patterns and fittings.
5. If there is any broken, worn, corroded, abraded or unravelling stitches the item should be rejected.

